



ARRANGE METHOD:



- Remark:**
- ① Cable: Cat. 6A SFTP, Stranded Bare Copper, 4Pairs Wires, 26AWG, Jacket PVC, OD: 6.5mm.
 - ② Plug: Cat. 6A Shielded Type Plug with 3 Prongs, 50u", 8P8C, UL94-V2, Mating Cycle >1200.
 - ③ Packing: 1PC/PE Bag with Label.
- Testing: 100% Cat. 6A Competent Test .
All materials are RoHS compliant.

ROHS

RELEASED
2017. 10. 10
R&D

CUT LINE AND ARRANGE CRITERION				CUT LINE AND ARRANGE CRITERION			
No.	Total length (MM)	no of patch cord	Cable tie (MM)	No.	Total length (MM)	no of patch cord	Cable tie (MM)
1	300	A	B	19	13000	B	C
2	500	/	/	20	14000		175
3	1000	/	/	21	15000		180
4	1500	175	60	22	16000		205
5	2000		70	23	17000		210
6	2500		80	24	18000		215
7	3000	185	95	25	19000		220
8	3500		100	26	20000		225
9	4000		110	27	25000	120	235
10	5000		120	28	30000		265
11	6000		130	29	40000		315
12	7000		135	30	50000		365
13	7500	135	140	31	60000		415
14	8000		145	32	70000		465
15	9000		150	33	80000		515
16	10000		165	34	90000		565
17	11000		170	35	100000		615
18	12000	120	175	36			665

WIRE CONNECTION TABLE								LENGTH		MOLD NO.	
white/ orange	white/ green	blue	white/ blue	white/ blue	green/ brown	white/ brown	A8	(+100)(+200)(+300)	02-117		
A1	A2	A3	A4	A5	A6	A7	A8				
B1	B2	B3	B4	B5	B6	B7	B8				

DWG. NO.

P6ASSB117-004

TITLE

CAT.6A SFTP PATCH CORD

UNIT	SCALE	SHEET
mm	1/1	1/1
DRAWN DATE	PROJ.	REV
2017/10/10	CHECKED	1
APPROVAL		DRAWN
Carine	Wuming	CathyLi